



Medium

## BESTRUN S1

BESTRUNS1

All-time favorite, low-cut safety shoe

|                 |                                      |
|-----------------|--------------------------------------|
| Upper           | Leather                              |
| Lining          | Nonwoven                             |
| Footbed         | SJ foam footbed                      |
| Midsole         | N/A                                  |
| Outsole         | PU/PU                                |
| Toecap          | Steel                                |
| Safety standard | S1 / SRC                             |
| Norms           | EN ISO 20345:2011<br>ASTM F2413:2018 |



BLK



### Oil & fuel resistant

The outsole is resistant against oil and fuel.



### Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



### Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

**Industries:**

Automotive, Chemical, Cleaning, Construction, Logistics, Mining, Oil &amp; Gas, Industry

**Environments:**

Dry environment, Uneven surfaces, Wet environment, Muddy environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|                | Description                                                      | Measure unit          | Result | EN ISO 20345 |
|----------------|------------------------------------------------------------------|-----------------------|--------|--------------|
| <b>Upper</b>   | <b>Leather</b>                                                   |                       |        |              |
|                | Upper: permeability to water vapor                               | mg/cm <sup>2</sup> /h | 2.2    | ≥ 0.8        |
|                | Upper: water vapor coefficient                                   | mg/cm <sup>2</sup>    | 25     | ≥ 15         |
| <b>Lining</b>  | <b>Nonwoven</b>                                                  |                       |        |              |
|                | Lining: permeability to water vapor                              | mg/cm <sup>2</sup> /h | 49.8   | ≥ 2          |
|                | Lining: water vapor coefficient                                  | mg/cm <sup>2</sup>    | 398    | ≥ 20         |
| <b>Footbed</b> | <b>SJ foam footbed</b>                                           |                       |        |              |
|                | Footbed: abrasion resistance                                     | cycles                | 400    | ≥ 400        |
| <b>Outsole</b> | <b>PU/PU</b>                                                     |                       |        |              |
|                | Outsole abrasion resistance (volume loss)                        | mm <sup>3</sup>       | 56     | ≤ 150        |
|                | Outsole slip resistance SRA: heel                                | friction              | 0.37   | ≥ 0.28       |
|                | Outsole slip resistance SRA: flat                                | friction              | 0.34   | ≥ 0.32       |
|                | Outsole slip resistance SRB: heel                                | friction              | 0.14   | ≥ 0.13       |
|                | Outsole slip resistance SRB: flat                                | friction              | 0.18   | ≥ 0.18       |
|                | Antistatic value                                                 | MegaOhm               | 120    | 0.1 - 1000   |
|                | ESD value                                                        | MegaOhm               | N/A    | 0.1 - 100    |
|                | Heel energy absorption                                           | J                     | 29     | ≥ 20         |
| <b>Toecap</b>  | <b>Steel</b>                                                     |                       |        |              |
|                | Impact resistance toecap (clearance after impact 100J)           | mm                    | N/A    | NA           |
|                | Compression resistance toecap (clearance after compression 10kN) | mm                    | N/A    | NA           |
|                | Impact resistance toecap (clearance after impact 200J)           | mm                    | 15     | ≥ 14         |
|                | Compression resistance toecap (clearance after compression 15kN) | mm                    | 17     | ≥ 14         |

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and maynot be used or reproduced in any format, without written consent from us.